



## High Performance Petrol System Cleaner LPG

Print date: 14.09.2011

Product code: 559

Page 1 of 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product identifier

High Performance Petrol System Cleaner LPG

#### Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cleaning agent for Fuel Systems

#### Details of the supplier of the safety data sheet

Company name:	CTP-GmbH	
Street:	Saalfelder Straße 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	

#### Further Information

Article Number: 33345, 33346

### SECTION 2: Hazards identification

#### Classification of the substance or mixture

Indications of danger : Highly flammable, Harmful, Irritant

R-phrases:

Highly flammable.

Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

#### Label elements

Danger symbols: F - Highly flammable; Xn - Harmful



F - Highly flammable

Xn - Harmful

#### Hazardous components which must be listed on the label

Distillates (petroleum, gasoline), hydrotreated light

#### R phrases

- |       |   |
|-------|---|
| 11    | Highly flammable.   |
| 36    | Irritating to eyes.   |
| 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| 65    | Harmful: may cause lung damage if swallowed.  |

#### S phrases

- |    |   |
|----|---|
| 02 | Keep out of the reach of children.  |
| 46 | If swallowed, seek medical advice immediately and show this container or label. |

### SECTION 3: Composition/information on ingredients

#### Mixtures



**High Performance Petrol System Cleaner LPG**

Print date: 14.09.2011

Product code: 559

Page 2 of 8

**Chemical characterization**

Surface tension compounds  
Detergents, Dispersants  
Synthetic agent combinations  
Anti wear agents not classified

Sum of ingredients:  
20 - 60 %

**Hazardous components**

EC No.	Chemical name	Quantity
CAS No.	Classification	
Index No.	GHS classification	
REACH No.		
265-149-8	Distillates (petroleum, gasoline), hydrotreated light	75 - 80 %
64742-47-8	Xn R10-65	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411	
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	10 - 15 %
67-63-0	F, Xi R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
	isononylphenole, ethoxylised	1 - 5 %
37205-87-1	Xn, Xi, N R22-41-51-53	
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 2; H302 H318 H411	
265-198-5	Naphtha (petroleum)	1 - 5 %
64742-94-5	Xn, Xi, N R36/38-51-53-65	
	Eye Irrit. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2; H319 H315 H304 H411	
-	Alcohol propoxilised	1 - 5 %
Polymer	R52-53	
	Aquatic Chronic 3; H412	
202-049-5	naphthalene	< 1 %
91-20-3	Carc. Cat. 3, Xn, N R40-22-50-53	
601-052-00-2	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410	

Full text of R- and H-phrases: see section 16.

**SECTION 4: First aid measures**

**Description of first aid measures**

**General information**

Move victim to fresh air. Put victim at rest and keep warm.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of Water and soap.

Rub in high-fat content cream.

**After contact with eyes**

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.



## High Performance Petrol System Cleaner LPG

Print date: 14.09.2011

Product code: 559

Page 3 of 8

### **After ingestion**

Let water be swallowed in little sips (dilution effect). Consult physician.

### **Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

### **Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

## SECTION 5: Firefighting measures

### **Extinguishing media**

#### **Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

#### **Extinguishing media which must not be used for safety reasons**

High power water jet.

### **Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

### **Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

### **Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

## SECTION 6: Accidental release measures

### **Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. No smoking.

### **Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

### **Methods and material for containment and cleaning up**

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

## SECTION 7: Handling and storage

### **Precautions for safe handling**

#### **Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition. No smoking. Take precautionary measures against static discharges.



## High Performance Petrol System Cleaner LPG

Print date: 14.09.2011

Product code: 559

Page 4 of 8

### Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### Further information on storage conditions

Packaging materials: metal.

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### Exposure limits (EH40)

CAS No.	Chemical name	ml/m <sup>3</sup>	mg/m <sup>3</sup>	F/ml	Category	Origin
91-20-3	Naphthalene	-	-	-	TWA (8 h)	CHAN
		-	-	-	STEL (15 min)	CHAN
67-63-0	Propan-2-ol	400	999	-	TWA (8 h)	WEL
		500	1250	-	STEL (15 min)	WEL

### Exposure controls

#### Protective and hygiene measures

When using do not eat, drink or smoke.

"Wash hands when done working with material; at breaks, lunch, shift changes, etc."

#### Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

#### Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN 374)

#### Eye protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

#### Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Physical state: liquid  
Colour: light red  
Odour: aromatic

#### Test method

#### Changes in the physical state

Boiling point: 110 - 116 °C  
Flash point: 12 °C  
Lower explosion limits: 0,6 vol. %  
Upper explosion limits: 12 vol. %  
Ignition temperature: > 200 °C  
Vapour pressure: 20 hPa  
(at 20 °C)  
Density (at 20 °C): 0.78-0.82 g/cm<sup>3</sup>



## High Performance Petrol System Cleaner LPG

Print date: 14.09.2011

Product code: 559

Page 5 of 8

Water solubility: insoluble  
(at 20 °C)

Solubility in other solvents: Organic solvents

### SECTION 10: Stability and reactivity

#### Conditions to avoid

Only use material in places where open light, fire and other sources of ignition can be kept away.

#### Incompatible materials

Oxidizing agents, acid, concentrated. Alkalis (alkalis), concentrated.

#### Hazardous decomposition products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity

CAS No.	Chemical name				
	Exposure routes	Method	Dose	Species	h
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light				
	Acute oral toxicity	LD50	>15000 mg/kg	rat.	
	Acute dermal toxicity	LD50	3400 mg/kg	rat.	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Acute oral toxicity	LD50	5280 mg/kg	rat.	
	Acute dermal toxicity	LD50	12800 mg/kg	Rabbit.	
	Acute inhalation toxicity	LC50	47,5 mg/l	rat.	4
37205-87-1	isononylphenole, ethoxylised				
	Acute oral toxicity	LD50	2000 mg/kg	rat.	
64742-94-5	Naphtha (petroleum)				
	Acute oral toxicity	LD50	>2000 mg/kg	rat.	
	Acute dermal toxicity	LD50	>2000 mg/kg	Rabbit.	
91-20-3	naphthalene				
	Acute oral toxicity	ATE	500 mg/kg		

##### Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

### SECTION 12: Ecological information

**High Performance Petrol System Cleaner LPG**

Print date: 14.09.2011

Product code: 559

Page 6 of 8

**Toxicity**

CAS No.	Chemical name				
	Aquatic toxicity	Method	Dose	Species	h
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light				
	Acute fish toxicity	LC50	10 mg/l	Oncorhynchus mykiss	96
	Acute algae toxicity	ErC50	4,6 mg/l	Pseudokirchneriella subcapitata	72
	Acute crustacea toxicity	EC50	10 mg/l	Daphnia magna	48
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Acute fish toxicity	LC50	9640 mg/l	Pimephales promelas	96
	Acute algae toxicity	ErC50	1000 mg/l	Algae	72
	Acute crustacea toxicity	EC50	13299 mg/l	Daphnia magna	48
37205-87-1	isononylphenole, ethoxylised				
	Acute fish toxicity	LC50	1-10 mg/l	Brachydanio rerio	96
	Acute algae toxicity	ErC50	1-10 mg/l	Scenedesmus subspicatus	72
64742-94-5	Naphtha (petroleum)				
	Acute fish toxicity	LC50	1-10 mg/l	Fish	96
	Acute algae toxicity	ErC50	1-10 mg/l	Algae	72
	Acute crustacea toxicity	EC50	1-10 mg/l	Daphnia magna	48

**Bioaccumulative potential**

Swims on the water. Low potential of bio-accumulation.

**SECTION 13: Disposal considerations**

**Waste treatment methods**

**Advice on disposal**

Do not dispose with household waste.  
Do not empty into drains or the aquatic environment.  
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.  
Arrange about the exact waste code with the local waste disposal expert.

**Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.  
Do not pierce, cut up or weld unclean container. (Explosion hazard.)

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**UN number:** UN1993  
**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**Transport hazard class(es):** 3  
**Packing group:** II  
**Hazard label:** 3



**Classification code:** F1

**High Performance Petrol System Cleaner LPG**

Print date: 14.09.2011

Product code: 559

Page 7 of 8

Special Provisions: 274 601 640C  
 Limited quantity: 1 L  
 Transport category: 2  
 Hazard-no.: 33  
 Tunnel restriction code: D/E

**Inland waterways transport**

**UN number:** UN1993  
**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**Transport hazard class(es):** 3  
**Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Special Provisions: 274 601 640C  
 Limited quantity: 1 L

**Marine transport**

**UN number:** UN1993  
**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**Transport hazard class(es):** 3  
**Packing group:** II  
 Hazard label: 3



Marine pollutant: -  
 Special Provisions: 274  
 Limited quantity: 1 L  
 EmS: F-E, S-E

**Air transport**

**UN/ID number:** UN1993  
**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**Transport hazard class(es):** 3  
**Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity Passenger: 1 L  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**Environmental hazards**



**High Performance Petrol System Cleaner LPG**

Print date: 14.09.2011

Product code: 559

Page 8 of 8

Dangerous for the environment: no

**SECTION 15: Regulatory information**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

**Additional information**

- Contains:  
> 30 % aliphatic hydrocarbons  
< 5 % Phenols and halogenated phenols

**National regulatory information**

Water contaminating class (D): 2 - water contaminating

**SECTION 16: Other information**

**Full text of R-phrases referred to under sections 2 and 3**

- |       |   |
|-------|---|
| 10    | Flammable.  |
| 11    | Highly flammable.   |
| 22    | Harmful if swallowed.   |
| 36    | Irritating to eyes.   |
| 36/38 | Irritating to eyes and skin.  |
| 40    | Limited evidence of a carcinogenic effect.  |
| 41    | Risk of serious damage to eyes.   |
| 50    | Very toxic to aquatic organisms.  |
| 51    | Toxic to aquatic organisms.   |
| 52    | Harmful to aquatic organisms.   |
| 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| 53    | May cause long-term adverse effects in the aquatic environment.                               |
| 65    | Harmful: may cause lung damage if swallowed.  |
| 67    | Vapours may cause drowsiness and dizziness.   |

**Full text of H-Statements referred to under sections 2 and 3**

- |      |   |
|------|---|
| H225 | Highly flammable liquid and vapour.                   |
| H226 | Flammable liquid and vapour.                          |
| H302 | Harmful if swallowed.                                 |
| H304 | May be fatal if swallowed and enters airways.         |
| H315 | Causes skin irritation.                               |
| H318 | Causes serious eye damage.                            |
| H319 | Causes serious eye irritation.                        |
| H336 | May cause drowsiness or dizziness.                    |
| H351 | Suspected of causing cancer.                          |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects.      |
| H412 | Harmful to aquatic life with long lasting effects.    |

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.  
The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*