

## EXPRESS POLISH

### Acryl PTFE-Polish

<b>Product properties:</b>	A special product for the maintenance and sealing of new, nearly new and even weathered Metallic -, multi-layer and effect lacquered paintwork finishes. Small surface scratches are covered and the product lends a radiating gloss to the paintwork again. All smooth surfaces, such as metal, chrome, copper, plastics, marble, tiles and enamel can be maintained. The surfaces are covered with a protective polymer layer, i.e. covered with a weather-resistant, sealed-surface, hard gloss layer which provides a long term base resistance to all external influences of the weather, such as sour rain, UV-rays, industrial fall-out contamination, ice-thawing salts and oils. Even tar, rust and insect remains are then easily removed.
<b>Areas of application:</b>	Vehicle maintenance and vehicle preparation. For manual or machine application.
<b>Dilution:</b>	To be used pure
<b>Instructions for use:</b>	Wash, rinse well with clean water and dry the surfaces before application. The polish is applied thinly and evenly by hand or with a buffing machine. The pressure applied during polishing should be adapted according to the state of the paintwork. The polish can be polished out immediately or more easily after drying out on the paintwork.
<b>Note:</b>	The Polish can be applied on wet or drying paintwork and it can also be applied in the sun!
<b>Frost susceptibility:</b>	Yes
<b>Available container size:</b>	500 ml
<b>Article number:</b>	16027

care  
max<sup>TM</sup>



**CTP GmbH**  
Saalfelder Straße 35  
07338 Leutenberg  
Tel.: 03 67 34/ 23 00  
Fax: 03 67 34/ 2 30 22  
hotline@ctp-gmbh.de